

## Product Availability

PRODUCT	2.5 mm (0.10)	5.0 (0.20)	0.25 (0.01)	0.51 (0.02)	0.7 (1/32)	1.59 (1/16)	2.38 (3/32)	3.18 (1/8)	4.76 (3/16)	6.35 (1/4)	9.52 (3/8)	12.7 (1/2)	15.9 (5/8)	19.0 (3/4)	25.4 (1)
BF-2000								•	•	•	•	•			
BF-1000						•	•	•	•	•	•	•	•	•	•
HT-870						•	•	•	•	•	•	•			
HT-800					• not red	•	•	•	•	•	•	•			
HT-820					•	•	•	•	•	•					
HT-840						•	•	•	•	•					
RF-120	•	•						▲	▲	▲	▲	▲	▲	▲	▲
IF-200		•						▲	▲	▲	▲	▲	▲	▲	▲
FPC						•	▲	•	▲	•					
HT-1240				▲	•	•	•	•	▲	▲					
HT-1250				▲	•	•	•	•	▲	▲					
HT-1260				▲	•	•	•	•	▲	▲					
HT-1270					•	•	•	•	▲	▲					
HT-1500					• not w/ adhesive	•	•	•							
HT-1510						•	▲	▲							
HT-6210			• not w/ adhesive	• not w/ adhesive	• not w/ adhesive	• not w/ adhesive	• not w/ adhesive	• not w/ adhesive							
HT-6220			• not w/ adhesive	• not w/ adhesive	• not w/ adhesive	• not w/ adhesive	• not w/ adhesive	• not w/ adhesive							
HT-6135			• not w/ adhesive	• not w/ adhesive	•	•	▲	▲							
HT-6240			• not w/ adhesive	• not w/ adhesive	•	•	▲	•							
HT-6360				• not w/ adhesive	•	•	▲	•							
HT-200	Sold by weight only, not thickness. Standard weights listed in price page 6. Also available with adhesive ( one side only) and/or fiberglass on one or two sides.														
<b>LEGEND</b>															
•	STANDARD PRODUCT														
▲	CUSTOM PRODUCT (Ask a Rogers Customer Service Representative for ordering details.)														
	PRODUCT NOT AVAILABLE														
Unless otherwise noted, all items shown on the Standard Availability Chart with a "•" or "▲" may be ordered with acrylic adhesive (on one side or two sides), silicone adhesive (on one side only) and/or slit to desired width.															

The information contained in this Availability Sheet is intended to assist you in designing with Rogers BISCO Silicones. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this Availability Sheet will be achieved by a user for a particular purpose. The user should determine the suitability of Rogers BISCO Silicones for each application.

The world runs better with Rogers.®